

Code: BR700ELCD-FR/UPS

UPS **BR700ELCD-FR/UPS** 700 VA CyberPower

The BR700ELCD-FR/UPS UPS is a professional device used to maintain the operation of the components connected to it.



Nominal power:	420 W
Apparent Power:	700 VA
Input voltage:	165 ... 290 V AC
Input frequency:	45 ... 65 Hz
Output voltage:	220 ... 240 V AC $\pm$ 5 % (Approximated Sine Wave) 5 V DC / 1 A @ USB
Output frequency:	50 / 60 Hz $\pm$ 1 %
Typical battery charge time:	8 hours
Battery:	1 pcs RBP0083
Estimated battery operation time:	• 47 minutes @ 60 W • 28 minutes @ 90 W
Number of outputs:	• 4 pcs - Battery backup, • 4 pcs - Overvoltage protection, • 1 pcs - USB, • 2 pcs - RJ11 / RJ45
Transfer time:	4 ms
Management software:	PowerPanel Personal Edition
Protections:	• Overvoltage, • Overload protection, • Phone/Fax/Modem and DSL/Network protection : RJ11 / RJ45

Main features:	• Sound signaling • LED indication • LCD display: operation mode, battery charging level, in/out voltage level • Low battery level alarm • Auto restart and charging
Application:	• Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Desktop
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	5.64 kg
Dimensions:	285 x 160 x 118 mm
Manufacturer / Brand:	CyberPower
Guarantee:	2 years