

Code: APTI-201F2-28WP IP CAMERA **APTI-201F2-28WP** - 1080p 2.8 mm

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

- 1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
- 2. Improper results of operation of the product or products related with it;
- 3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.



Code: APTI-201F2-28WP IP CAMERA **APTI-201F2-28WP** - 1080p 2.8 mm

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p. Included camera software enables management and integrated monitoring of many network cameras. The range of IR illumination according to the manufacturer

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	1/2.7 " CMOS
Digital Image Processor:	Fullhan FH8830
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm, 3.0 Mpx
View angle:	• 88 ° (manufacturer data) • 110 ° (our tests result)
Range of IR illumination:	20 m
Image compression method:	H.264+ / H.264
Alarm inputs / outputs:	1
Bitrate:	64 12000 kbps
Main stream frame rate:	max. 25 fps - 1080p
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
WEB Server:	Built-in
Max. number of on-line users:	10
ONVIF:	2.4





Code: APTI-201F2-28WP IP CAMERA **APTI-201F2-28WP** - 1080p 2.8 mm

	Main features:	ICR - Movable InfraRed filter Flicker Control - The technology eliminates the tiring eyes flickering image effect Possibility to change the resolution, quality and bit rate BLC - Back Light Compensation Motion Detection Privacy zones Mirror - Mirror image Day/Night mode - configurable
Default admin user / password: Web browser access ports: 80 PC client access ports: 80 Mobile client access ports: 80 RTSP URL: RTSP URL: rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream Color: White Power supply: • PoE (802.3af), • 12 V DC / 370 mA Power consumption: ≤ 4.5 W Housing: "Index of Protection": "Index of Protection": Poeration temp: -20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Mobile phones support:	Android: Free application <u>FREEIP</u>
Web browser access ports: 80 PC client access ports: 80 Mobile client access ports: 80 Port ONVIF: 80 RTSP URL: rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream Color: White Power supply: • PoE (802.3af),	Default IP address:	192.168.1.168
PC client access ports: 80 Mobile client access ports: 80 Port ONVIF: 80 RTSP URL: rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream rtsp://user:password@ip_address:80/1 - Sub stream rtsp://user:password@ip_address:80/1 - Sub stream Power supply: • PoE (802.3af), • 12 V DC / 370 mA Power consumption: ≤ 4.5 W Housing: "Index of Protection": Dome - Metal + Plastic "Index of Protection": Operation temp: -20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: Description of the stream results of the st	Default admin user / password:	admin / admin
Mobile client access ports: 80 Port ONVIF: 80 RTSP URL: rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream Color: White Power supply: • PoE (802.3af), • 12 V DC / 370 mA Power consumption: ≤ 4.5 W Housing: Dome - Metal + Plastic "Index of Protection": IP66 Operation temp: -20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: 0.21 kg English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Web browser access ports:	80
Port ONVIF: 80 RTSP URL: rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream Color: White Power supply: Power consumption: 4.5 W Housing: Dome - Metal + Plastic "Index of Protection": IP66 Operation temp: -20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	PC client access ports:	80
RTSP URL: rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream Color: White Power supply: - PoE (802.3af), - 12 V DC / 370 mA Power consumption: ≤ 4.5 W Housing: Dome - Metal + Plastic "Index of Protection": IP66 Operation temp: -20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: 0.21 kg English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Mobile client access ports:	80
rtsp://user:password@ip_address:80/1 - Sub stream Color: White Power supply: Power consumption: ≤ 4.5 W Housing: Dome - Metal + Plastic "Index of Protection": IP66 Operation temp: 20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Port ONVIF:	80
Power supply: Power consumption: \$\frac{12 \text{ V DC / 370 mA}}{270 mA}\$ Power consumption: \$\frac{4.5 \text{ W}}{2.5 \text{ V DC / 370 mA}}\$ Fower consumption: \$\frac{4.5 \text{ W}}{2.5 \text{ V DC / 370 mA}}\$ Fower consumption: \$1000000000000000000000000000000000000	RTSP URL:	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Power supply: - 12 V DC / 370 mA Power consumption: ≤ 4.5 W Housing: Dome - Metal + Plastic "Index of Protection": IP66 Operation temp: -20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Color:	White
Housing: "Index of Protection": IP66 Operation temp: -20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: Display and the plastic English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Power supply:	
"Index of Protection": Operation temp: -20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: 0.21 kg English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Power consumption:	≤ 4.5 W
Operation temp: -20 °C 55 °C Dimensions: Ø 87 x 73 mm Weight: 0.21 kg English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Housing:	Dome - Metal + Plastic
Dimensions: Ø 87 x 73 mm Weight: 0.21 kg English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	"Index of Protection":	IP66
Weight: 0.21 kg English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Operation temp:	-20 °C 55 °C
English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Heb	Dimensions:	Ø 87 x 73 mm
	Weight:	0.21 kg
Supported languages: Spanish, Dutch, Japanese, Korean, German, Persian, Polish, Portuguese, Russian Turkish, Italian	Supported languages:	English, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, French, Hebrew, Spanish, Dutch, Japanese, Korean, German, Persian, Polish, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand: APTI	Manufacturer / Brand:	APTI
Guarantee: 2 years	Guarantee:	2 years


Camera is out from clamping ring:



Code: APTI-201F2-28WP IP CAMERA **APTI-201F2-28WP** - 1080p 2.8 mm



Mounting side view:



In the kit:



Code: APTI-201F2-28WP IP CAMERA **APTI-201F2-28WP** - 1080p 2.8 mm



Configuration and operation of the FreeIP cloud:

:

PACKAGE

Dimensions (L x W x H): 0x0x0 mm

Gross Weight: 0 kg