

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity; 2. Improper results of operation of the product or products related with it;

3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

parameters in DVR settings without any problem.

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.





DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



User Manual Code: APTI-N1611-M5 NVR **APTI-N1611-M5** 16 CHANNELS

Standard:	TCP/IP	
Supported resolutions:	max. 5 Mpx - 2592 x 1944 px	
Video outputs:	1 pcs HDMI 1 pcs VGA	
Audio support:	16 Channels - Audio from cameras	
Audio inputs:	-	
Audio outputs:	1 pcs Jack 3.5 mm socket	
Image compression method:	H.265+ / H.265 / H.264+ / H.264	
USB:	2 pcs USB 2.0	
Supported hard drives:	1 x 8 TB SATA	
Recording modes:	Manual, Motion Detection, Schedule	
Network protocols:	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, P2P, ONVIF 2.4	
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)	
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast Playback max. 4 cameras in the same time	
Bitrate:	80 Mbps	
Network functions:	Network Client Software and IE browser: live view, playback and backup of the	
	records, configuration of the recorder parameters	
ONVIF:		
ONVIF: Mobile phones support:		
	 Port no.: 6000 or access by a cloud (P2P) Android: Free application BitVision, Android: Free application iVMS320 	
Mobile phones support:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application <u>BitVision</u>, Android: Free application <u>iVMS320</u> Android: Free application <u>BitVision</u>, iOS: Free application <u>iVMS320</u> 	
Mobile phones support: Default IP address:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application <u>BitVision</u>, Android: Free application <u>iVMS320</u> Android: Free application <u>BitVision</u>, iOS: Free application <u>iVMS320</u> 192.168.1.88 	
Mobile phones support: Default IP address: Default admin user / password:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application BitVision, Android: Free application iVMS320 Android: Free application BitVision, iOS: Free application iVMS320 192.168.1.88 admin / 12345 	
Mobile phones support: Default IP address: Default admin user / password: Web browser access ports:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application <u>BitVision</u>, Android: Free application <u>iVMS320</u> Android: Free application <u>BitVision</u>, iOS: Free application <u>iVMS320</u> 192.168.1.88 admin / 12345 80, 5000, 554 	
Mobile phones support: Default IP address: Default admin user / password: Web browser access ports: PC client access ports:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application <u>BitVision</u>, Android: Free application <u>iVMS320</u> Android: Free application <u>BitVision</u>, iOS: Free application <u>iVMS320</u> 192.168.1.88 admin / 12345 80, 5000, 554 80, 5000, 554 	
Mobile phones support: Default IP address: Default admin user / password: Web browser access ports: PC client access ports: Mobile client access ports:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application BitVision, Android: Free application iVMS320 Android: Free application BitVision, iOS: Free application iVMS320 192.168.1.88 admin / 12345 80, 5000, 554 80, 5000, 6000 	
Mobile phones support: Default IP address: Default admin user / password: Web browser access ports: PC client access ports: Mobile client access ports: Operation temp:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application BitVision, Android: Free application iVMS320 Android: Free application BitVision, iOS: Free application iVMS320 192.168.1.88 admin / 12345 80, 5000, 554 80, 5000, 6000 -10 °C 55 °C 	
Mobile phones support: Default IP address: Default admin user / password: Web browser access ports: PC client access ports: Mobile client access ports: Operation temp: Alarm inputs / outputs:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application BitVision, Android: Free application iVMS320 Android: Free application BitVision, iOS: Free application iVMS320 192.168.1.88 admin / 12345 80, 5000, 554 80, 5000, 6000 -10 °C 55 °C 	
Mobile phones support:Default IP address:Default admin user / password:Web browser access ports:Web browser access ports:PC client access ports:Mobile client access ports:Operation temp:Alarm inputs / outputs:PTZ control:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application <u>BitVision</u>, Android: Free application <u>iVMS320</u> Android: Free application <u>BitVision</u>, iOS: Free application <u>iVMS320</u> 192.168.1.88 admin / 12345 80, 5000, 554 80, 5000, 554 80, 5000, 6000 -10 °C 55 °C IP Speed Dome Cameras 	
Mobile phones support:Default IP address:Default admin user / password:Web browser access ports:Web browser access ports:PC client access ports:Mobile client access ports:Operation temp:Alarm inputs / outputs:PTZ control:Motion Detection:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application BitVision, Android: Free application iVMS320 Android: Free application BitVision, iOS: Free application iVMS320 192.168.1.88 admin / 12345 80, 5000, 554 80, 5000, 554 80, 5000, 6000 -10 °C 55 °C IP Speed Dome Cameras Split the screen into zones : 24 x 18 motion zones 	
Mobile phones support:Default IP address:Default admin user / password:Web browser access ports:PC client access ports:Mobile client access ports:Operation temp:Alarm inputs / outputs:PTZ control:Motion Detection:Mouse support:	 Port no.: 6000 or access by a cloud (P2P) Android: Free application BitVision, Android: Free application iVMS320 Android: Free application BitVision, iOS: Free application iVMS320 192.168.1.88 admin / 12345 80, 5000, 554 80, 5000, 554 80, 5000, 6000 -10 °C 55 °C IP Speed Dome Cameras Split the screen into zones : 24 x 18 motion zones 	
Mobile phones support:Default IP address:Default admin user / password:Web browser access ports:PC client access ports:Mobile client access ports:Operation temp:Alarm inputs / outputs:PTZ control:Motion Detection:Mouse support:IR remote controller in the set:	 ✓ Port no.: 6000 or access by a cloud (P2P) Android: Free application BitVision, Android: Free application iVMS320 Android: Free application BitVision, iOS: Free application iVMS320 192.168.1.88 admin / 12345 80, 5000, 554 80, 5000, 6000 -10 °C 55 °C IP Speed Dome Cameras Split the screen into zones : 24 x 18 motion zones ✓ IP Speed Dome Cameras Split the screen into zones : 24 x 18 motion zones ✓ IP Speed Dome Cameras Split the screen into zones : 24 x 18 motion zones ✓ IP Speed Dome Cameras Split the screen into zones : 24 x 18 motion zones ✓ IP Speed Dome Cameras Split the screen into zones : 24 x 18 motion zones ✓	





User Manual Code: APTI-N1611-M5 NVR **APTI-N1611-M5** 16 CHANNELS

Supported languages:	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	APTI
Guarantee:	2 years

Top view:



Rear panel:



See how to mount a hard disk drive and configure the recorder: : In the kit:



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-04-17

APTI-N1611-M5





PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

