

Code: SD50225I-HC-S3
AHD, HD-CVI, HD-TVI SPEED DOME CAMERA OUTDOOR **SD50225I-HC-S3** - 1080p 4.8 ... 120 mm
DAHUA

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

- 1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
- 2. Improper results of operation of the product or products related with it;
- 3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.

2024-04-25 SD50225I-HC-S3 1/7



 ${\bf Code: SD50225I\text{-}HC\text{-}S3} \\ {\bf AHD, HD\text{-}CVI, HD\text{-}TVI SPEED DOME CAMERA OUTDOOR $\bf SD50225I\text{-}HC\text{-}S3} - 1080p~4.8~...~120~mm~} \\ {\bf DAHUA}$

Megapixel camera with 1/2.8" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL. The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image. Camera is according to IP67 Index of Protection norm.

Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.



| Standard: | AHD, HD-CVI, HD-TVI, CVBS |
|---|---|
| Sensor: | 1/2.8 " STARVIS™ CMOS |
| Matrix size: | 2.1 Mpx |
| Resolution: | 1920 x 1080 - 1080p 1280 x 720 - 720p |
| IR illuminator: | 1 |
| Lens: | 4.8 120 mm |
| View angle: | • 63 ° 2.6 ° (manufacturer data) • 56 ° 3.4 ° (our tests result) |
| Optical zoom: | x 25 |
| Digital zoom: | x 16 |
| Rotation speed depending on ZOOM level: | > |
| Horizontal rotation range: | 360 ° continuous |
| Vertical rotation range: | 0 ° 90 ° |
| Rotation speed (manual control): | 0.1 °/s 350 °/s (horizontal) , 0.1 °/s 250 °/s (vertical) |
| Preset rotation speed: | max. 500 °/s |



$Code: SD50225I\text{-HC-S3} \\ \text{AHD, HD-CVI, HD-TVI SPEED DOME CAMERA OUTDOOR $\textbf{SD50225I-HC-S3}$ - 1080p 4.8 ... 120 mm \\ \text{DAHUA} \\$

| PTZ control: Nia interface RS-485 The ability to control via coaxial cable from recorder DAHUA, BCS, RAPID Protocols: Pelco-D, Pelco-P, DH-SD (auto detection) S/N ratio: > 55 dB Video output: AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp 75 Ω Audio: External microphone input Number of presets: 300 Route settings: 8 Horizontal scan: ✓ Park action: Call the set function (tour, scan, etc.) after specified dwell time Alarm inputs / outputs: 2 / 1 WDR-120 dB - Wide Dynamic Range 20-DNR, 3D-DNR - Digital Noise Reduction BLC - Back Light Compensation 11C - High Light Compensation (spot) HIC - High Light Compensation 12C - High Light Compensation HIC - High Light Compensation 12C - High Light Compensation A Configurable Privacy Zones 24 Configurable Privacy Zones - Year Supply: 24 V AC / 1.5 A (power adapter included) Power consumption: ≤ 23 W Housing: Speed Dome, Metal Color: White "Index of Protoction": IP67 Vanda-proof: IK10 Operation temp: 40 °C 60 °C <th></th> <th></th> | | |
|--|-------------------------|---|
| S/N ratio: > 55 dB Video output: AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp 75 Ω Audio: External microphone input Number of presets: 300 Route settings: 8 Horizontal scan: ✓ Park action: Call the set function (tour, scan, etc.) after specified dwell time Alarm inputs / outputs: 2 / 1 **WDR - 120 dB · Wide Dynamic Range - 2D-DNR, 3D-DNR - Digital Noise Reduction - BLC - Back Light Compensation (spot) - HLC - High Light Compensation + HLC - High Light Compensation + HLC - High Light Compensation (spot) - HLC - Auto White Balance - 24 Configurable Privacy Zones - The camera is equipped with a built-in heater with a thermostat, OSD menu: OSD menu available via DAHUA recorder Power consumption: ≤ 23 W Housing: Speed Dome, Metal Color: White *Index of Protection*: IP67 Vandal-proof: IK10 Operation temp: 40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: Banufacturer / Brand: DAHUA DAHUA | PTZ control: | |
| Aldio: External microphone input Audio: Sumber of prosets: 300 Route settings: 8 Horizontal scan: ✓ Park action: Alarm inputs / outputs: 2 / 1 WDR - 120 dB - Wide Dynamic Range - 2D-DNR, 3D-DNR - Digital Noise Reduction - BLC - Back Light Compensation - BLC - Back Light Compensation (spot) - ICR - Movable InfraRed filter - Auto White Balance - 24 Configurable Privacy Zones - 24 Configurable Privacy Zones - 14 Consumption: Speed Dome, Metal Color: White "Index of Protection": Weight: Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: Bank Light, Very 2 vones - 24 Van (with Bank) - 25 Weight: Supported languages: Bank Light Compensation (spot) - ICR - Movable InfraRed filter - 24 Van (with Bank) - 24 Van (with Bank) - 24 Van (with Bank) - 25 Weight: Weight: Supported languages: Bank Light Compensation (with bracket) - 26 Van (with bracket) - 27 Van (with bracket) - 28 Van (with bracket) - 29 Van (with bracket) - 20 V | Protocols: | Pelco-D, Pelco-P, DH-SD (auto detection) |
| Audio: External microphone input Number of presets: 300 Route settings: 8 Horizontal scan: ✓ Park action: Call the set function (tour, scan, etc.) after specified dwell time Alarm inputs / outputs: 2 / 1 WDR - 120 dB - Wide Dynamic Range - 2D-DNR, 3D-DNR - Digital Noise Reduction - BLC - Back Light Compensation (spot) - ICR - Movable InfraRed filter - Auto White Balance - 24 Configurable Privacy Zones Power supply: 24 V AC / 1.5 A (power adapter included) Power consumption: ≤ 23 W Housing: Speed Dome, Metal Color: White "Index of Protection*: IP67 Vandal-proof: IK10 Operation temp: 40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | S/N ratio: | > 55 dB |
| Number of presets: 8 | Video output: | AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp 75 Ω |
| Route settings: 8 Horizontal scan: ✓ Park action: Call the set function (tour, scan, etc.) after specified dwell time Alarm inputs / outputs: 2 / 1 WDR - 120 dB - Wide Dynamic Range - 2D-DNR, 3D-DNR - Digital Noise Reduction - BLC - Back Light Compensation BLC - Back Light Light Light Compensation BLC - Back Light Light Light Compensation BLC - Back Light Light Light Light Compensation BLC - Back Light Light Light Light Compensation BLC - Back Light Li | Audio: | External microphone input |
| Horizontal scan: Park action: Call the set function (tour, scan, etc.) after specified dwell time Alarm inputs / outputs: Z / 1 WWR - 120 dB - Wide Dynamic Range - 2D-DNR, 3D-DNR - Digital Noise Reduction - BLC - Back Light Compensation - BLC - Back Light Compensation (spot) - HLC - High Light Compensation (spot) - HLC - High Light Gomensation (spot) - HLC - High Light Compensation - BLC - Back Light Compensation - BLC - Back Light Compensation - HLC - High Light Gomensation - HLC | Number of presets: | 300 |
| Park action: Alarm inputs / outputs: 2 / 1 Main features: Main features: Main features: DSD menu: OSD menu: OSD menu: OSD menu: OSD menu available via DAHUA recorder Power consumption: Speed Dome, Metal Color: White "Index of Protection": White 1P67 Vandal-proof: Vandal-proof: Vandal-proof: Vandal-proof: Weight: 3.18 kg (with bracket) Dimensions: Balc. Back Light Compensation PULC - High Light Compensation (spot) PURC - Movable InfraRed filter - Auto White Balance - 2.24 Configurable Privacy Zones - The camera is equipped with a built-in heater with a thermostat , OSD menu available via DAHUA recorder Power consumption: ≤ 23 W Housing: Speed Dome, Metal Color: White "Index of Protection": Vandal-proof: IK10 Operation temp: 40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: Bnaufacturer / Brand: DAHUA | Route settings: | 8 |
| Alarm inputs / outputs: 2 / 1 | Horizontal scan: | ~ |
| WDR - 120 dB - Wide Dynamic Range 2D-DNR, 3D-DNR - Digital Noise Reduction BLC - Back Light Compensation HLC - High Light Compensation (spot) 1CR - Movable InfraRed filter Auto White Balance 24 V AC / 1.5 A (power adapter included) 24 V AC / 1.5 A (power adapter included) Power consumption: ≤ 23 W | Park action: | Call the set function (tour, scan, etc.) after specified dwell time |
| Audin features: 2D-DNR, 3D-DNR - Digital Noise Reduction | Alarm inputs / outputs: | 2/1 |
| Power supply: 24 V AC / 1.5 A (power adapter included) Power consumption: ≤ 23 W Housing: Speed Dome, Metal Color: White "Index of Protection": IP67 Vandal-proof: IK10 Operation temp: -40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | Main features: | 2D-DNR, 3D-DNR - Digital Noise Reduction BLC - Back Light Compensation HLC - High Light Compensation (spot) ICR - Movable InfraRed filter Auto White Balance 24 Configurable Privacy Zones |
| Power consumption: ≤ 23 W Housing: Speed Dome, Metal Color: White "Index of Protection": IP67 Vandal-proof: IK10 Operation temp: -40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | OSD menu: | OSD menu available via DAHUA recorder |
| Housing: Speed Dome, Metal Color: White "Index of Protection": IP67 Vandal-proof: IK10 Operation temp: -40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | Power supply: | 24 V AC / 1.5 A (power adapter included) |
| Color: White "Index of Protection": IP67 Vandal-proof: IK10 Operation temp: -40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | Power consumption: | ≤ 23 W |
| "Index of Protection": Vandal-proof: IK10 Operation temp: -40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | Housing: | Speed Dome, Metal |
| Vandal-proof: IK10 Operation temp: -40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | Color: | White |
| Operation temp: -40 °C 60 °C Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | "Index of Protection": | IP67 |
| Weight: 3.18 kg (with bracket) Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | Vandal-proof: | IK10 |
| Dimensions: 186 x 296 x 420 mm (with bracket) Supported languages: English, Polish Manufacturer / Brand: DAHUA | Operation temp: | -40 °C 60 °C |
| Supported languages: English, Polish Manufacturer / Brand: DAHUA | Weight: | 3.18 kg (with bracket) |
| Manufacturer / Brand: DAHUA | Dimensions: | 186 x 296 x 420 mm (with bracket) |
| | Supported languages: | English, Polish |
| Guarantee: 3 years | Manufacturer / Brand: | DAHUA |
| outlines. O yours | Guarantee: | 3 years |

Bottom view:



Code: SD50225I-HC-S3
AHD, HD-CVI, HD-TVI SPEED DOME CAMERA OUTDOOR **SD50225I-HC-S3** - 1080p 4.8 ... 120 mm
DAHUA



Bottom view (configuration switches visible):



Bracket dimensions:


2024-04-25 SD50225I-HC-S3 4/7



 ${\it Code: SD50225I-HC-S3} \\ {\it AHD, HD-CVI, HD-TVI SPEED DOME CAMERA OUTDOOR $\it SD50225I-HC-S3} - 1080p~4.8~...~120~mm \\ {\it DAHUA}$







Camera connectors:





Connectors description:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Gross Weight: 0 kg



 ${\it Code: SD50225I-HC-S3} \\ {\it AHD, HD-CVI, HD-TVI SPEED DOME CAMERA OUTDOOR $\it SD50225I-HC-S3} - 1080p~4.8~...~120~mm \\ {\it DAHUA}$