



User Manual

Code: ZP-2/TX
WIRELESS SYSTEM TRANSMITTER **ZP-2/TX**

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order.

If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
2. Improper results of operation of the product or products related with it;
3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.


The ZP-2 wireless system enables wireless control of devices using the ISM 433 MHz band. The remote control has 2 separate channels. Each channel is controlled by one dedicated input in the transmitter. From the receiver side, a separate NO/NC relay is assigned to each channel. The maximum load of each of the relays is 2300 W (AC), which makes the system suitable for a very wide range of applications.

The set of devices ZP-2 allows you to wirelessly control e.g. lighting, electric sprinklers, powering household appliances, etc. Using the system can also implement automatic control of shutters or gates. The method of controlling the ZP-2/TX transmitter also makes the device perfect for integration with access control and alarm systems, enabling the installation of e.g. door opening buttons, panic buttons or detectors in places where the laying of additional cables is difficult or impossible.



The system consists of a transmitter and a receiver, however, connections in any configuration are possible: (1:1, 1:N, N:1, N:N). You can assign a maximum of 128 transmitters to each of the receivers, while the number of receivers that can work with one transmitter is limited only by the transmission range.

The system enables operation in one of three modes: monostable (the relay is on as long as the input in the transmitter is closed), bistable (a momentary close of the input causes a change in the relay's operating state) and time (a momentary close of the input causes the relay state to change for a defined time).

Attention! The ZP-2/TX device requires the ZP-2/RX receiver for cooperation.



Operating range in open area:	to 300 m
Frequency band:	433 MHz
Number of inputs:	2
Operation modes:	<ul style="list-style-type: none"> • Monostable mode, • Bistable mode, • Time mode
Time adjustment range:	1 s ... 255 s
Operation temp:	-20 °C ... 60 °C
Weight:	0.010 kg
Dimensions:	38 x 30 x 20 mm
Power supply:	Battery type LS14250 (3.6V 1/2 AA/1.2Ah) - included
Manufacturer / Brand:	DELTA
Guarantee:	2 years



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------