

Code: BCS-V-TI236IR6-AI
IP VANDALPROOF CAMERA BCS-V-TI236IR6-AI - 1080p 2.8 ... 12 mm - MOTOZOOM BCS View

### Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

- 1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
- 2. Improper results of operation of the product or products related with it;
- 3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

#### Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

#### Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.



Code: BCS-V-TI236IR6-AI

IP VANDALPROOF CAMERA BCS-V-TI236IR6-AI - 1080p 2.8 ... 12 mm - MOTOZOOM BCS View

IP camera with efficient  $\rm H.264$  /  $\rm H.265$  image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

The used motozoom lens with  $2.8\dots 12$  mm focal length allows to remote view angle adjustment. PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install.

Camera is according to IP67 Index of Protection norm.



Standard:	TCP/IP
Sensor:	1/2.8 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens:	2.8 12 mm - Motozoom
View angle:	• 113 ° 31 ° (manufacturer data) • 108 ° 32 ° (our tests result)
Compression:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination:	60 m
Alarm inputs / outputs:	1/1
Main stream frame rate:	25 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv6, UDP, Bonjour, SSL / TLS
Audio:	External microphone input     Audio output     Bi-directional audio streaming support
WEB Server:	Built-in, NVR compliance



# 

Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Max. number of on-line users:	6
ONVIF:	18.12
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P)  • Android: Free application BCS View  • iOS (iPhone): Free application BCS View
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P)
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
RS-485 interface:	-
Main features:	Dark View Technology     WDR - 120 dB - Wide Dynamic Range     3D-DNR - Digital Noise Reduction     ROI - improve the quality of selected parts of image     BLC/HLC - Back Light / High Light Compensation     Auto White Balance     AGC - Automatic Gain Control     AES - Auto Electronic Shutter     Motion Detection     Configurable Privacy Zones     ICR - Movable InfraRed filter     Intelligent Image Analysis: intrusion, crossing the line (tripwire), scene changing, entering the marked area, leaving the marked area, face detection     Filtering of false alarms based on the recognition of persons and vehicles     CVBS, SPOT output     RESET button
Power supply:	• PoE (802.3at), • 12 V DC / 1200 mA
Power consumption:	≤ 15 W @ PoE (802.3at) ≤ 13.5 W @ 12 V DC
Housing:	Compact, Metal
Color:	White
"Index of Protection":	IP67
Vandal-proof:	IK10
Operation temp:	-30 °C 60 °C
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian



### Code: BCS-V-TI236IR6-AI

IP VANDALPROOF CAMERA  $\mathbf{BCS\text{-}V\text{-}T1236IR6\text{-}AI}$  - 1080p 2.8 ... 12 mm - MOTOZOOM BCS View

Weight:	1.7 kg
Dimensions:	Ø 144 x 333 mm
Manufacturer / Brand:	BCS View
Guarantee:	3 years

#### Front view:



### Side view:



Memory card slot:



Code: BCS-V-TI236IR6-AI
IP VANDALPROOF CAMERA **BCS-V-TI236IR6-AI** - 1080p 2.8 ... 12 mm - MOTOZOOM BCS View



#### Camera connectors:



Bracket view:



Code: BCS-V-TI236IR6-AI IP VANDALPROOF CAMERA **BCS-V-TI236IR6-AI** - 1080p 2.8 ... 12 mm - MOTOZOOM BCS View








Code: BCS-V-TI236IR6-AI

IP VANDALPROOF CAMERA BCS-V-TI236IR6-AI - 1080p 2.8 ... 12 mm - MOTOZOOM BCS View



#### Camera and bracket dimensions:



In the kit:



#### PACKAGE

Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg





Code: BCS-V-TI236IR6-AI
IP VANDALPROOF CAMERA **BCS-V-TI236IR6-AI** - 1080p 2.8 ... 12 mm - MOTOZOOM BCS View