

IP SPEED DOME CAMERA OUTDOOR **SD22404DB-GNY-W** Wi-Fi, - 4 Mpx 2.8 ... 12 mm DAHUA

#### Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

- 1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
- 2. Improper results of operation of the product or products related with it;
- 3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

#### Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

#### Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m.

Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-05-09 SD22404DB-GNY-W 1/6



# 

| Standard:                        | TCP/IP   |
|----------------------------------|--|
| Sensor:                          | 1/2.8 " STARVIS™ CMOS  |
| Matrix size:                     | 4 Mpx  |
| Resolution:                      | 2560 x 1440 - 4 Mpx,<br>2304 x 1296 - 3 Mpx,<br>1920 x 1080 - 1080p,<br>1280 x 960 - 1.3 Mpx,<br>1280 x 720 - 720p   |
| IR illuminator:                  | _  |
| Scanning system:                 | Progressive  |
| Lens:                            | 2.8 12 mm  |
| View angle:                      | • 90 ° 29 ° (manufacturer data)<br>• 82 ° 28 ° (our tests result)  |
| Optical zoom:                    | x 4  |
| Digital zoom:                    | x 16   |
| Min. illumination:               | 0.005 Lux (color)<br>0.0005 Lux (B/W)  |
| S/N ratio:                       | > 55 dB  |
| Preset rotation speed:           | 100 °/s (horizontal)<br>60 °/s (vertical)  |
| Rotation speed (manual control): | • 0.1 °/s 100 °/s (horizontal)<br>• 0.1 °/s 60 °/s (vertical)  |
| Horizontal rotation range:       | 0 ° 355 ° - Rotation of the head is limited by stops   |
| Vertical rotation range:         | 0 ° 90 °   |
| RS-485 interface:                | _  |
| Number of presets:               | 300  |
| Horizontal scan:                 | ~  |
| Route settings:                  | 8  |
| Image compression method:        | H.265+ / H.265 / H.264+ / H.264 / H.264H / MJPEG   |
| Audio:                           | -  |
| Alarm inputs / outputs:          | _  |
| Main stream frame rate:          | 25 fps @ 4 Mpx   |
| Network interface:               | • Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz<br>• 10/100 Base-T (RJ-45)  |
| Network protocols:               | IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, SAMBA, IEEE 802.1x |
| Memory card slot:                | Micro SD memory cards up to 512GB support (possible local recording)   |
| WEB Server:                      | Built-in   |
| Max. number of on-line users:    | 20   |



# Code: SD22404DB-GNY-W IP SPEED DOME CAMERA OUTDOOR **SD22404DB-GNY-W** Wi-Fi, - 4 Mpx 2.8 ... 12 mm DAHUA

| ONVIF:                         | 21.12   |
|--------------------------------|---|
| Mobile phones support:         | Port 37777  • Android: Free application <u>DMSS</u> • iOS (iPhone): Free application <u>DMSS</u>  |
| Default IP address:            | 192.168.1.108   |
| Default admin user / password: | admin / - The administrator password should be set at the first start   |
| Web browser access ports:      | 80, 37777   |
| PC client access ports:        | 37777   |
| Mobile client access ports:    | 37777   |
| Port ONVIF:                    | 80  |
| RTSP URL:                      | rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream  |
| Main features:                 | <ul> <li>D-WDR - Wide Dynamic Range</li> <li>2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>EIS - Electronic Image Stabilization</li> <li>BLC - Back Light Compensation</li> <li>HLC - High Light Compensation (spot)</li> <li>Motion Detection</li> <li>Configurable Privacy Zones</li> <li>Day/night mode</li> <li>ICR - Movable InfraRed filter</li> <li>AGC - Automatic Gain Control</li> <li>Sharpness - sharper image outlines</li> <li>SMD 3.0 - searching for an object classified as: human, motor vehicle</li> <li>IVS analysis, crossing the line (tripwire), intrusion - classification of people and vehicles, abandoned/missing object, detection of entry into the area / exit from the area, parking detection, fast moving, detection of people gathering, face detection - advanced face capture features</li> </ul> |
| Power supply:                  | 12 V DC / 400 mA  |
| Power consumption:             | ≤ 4.8 W   |
| Housing:                       | Speed Dome, Metal   |
| Color:                         | White   |
| Operation temp:                | -30 °C 60 °C  |
| "Index of Protection":         | IP66  |
| Vandal-proof:                  | IK10  |
| Weight:                        | 0.57 kg   |
| Dimensions:                    | Ø 122 x 89 mm   |
| Supported languages:           | Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian  |
| Manufacturer / Brand:          | DAHUA   |
| Guarantee:                     | 3 years   |



IP SPEED DOME CAMERA OUTDOOR **SD22404DB-GNY-W** Wi-Fi, - 4 Mpx 2.8 ... 12 mm DAHUA

Camera view after remove the Dome cover:



#### Memory card slot:



Camera mounting dimensions:

2024-05-09 SD22404DB-GNY-W 4/6





See how to initialize DAHUA cameras:

:


Example captures of device interface:











In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg

