

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity; 2. Improper results of operation of the product or products related with it;

3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.





The smart lock allows you to remotely open the door to your home, apartment or business.

The TEDEE-PRO/GR lock can be mounted on European profile cylinders, it is recommended to use dedicated Gerda SLR series cylinders. Easy and quick installation on the inside of the door makes the lock invisible to outsiders.

It is possible to operate the device from the mobile application on the Android, iOS systems via the Bluetooth / Wi-Fi connection. For the proper management of the device, it is necessary to install the Tedee mobile application. Tedee application works perfectly with Google Assistant, Amazon Alexa, Apple Siri and many others, which allows you to control connected devices using voice commands. It provides features such as remote operation, notifications, activity log, auto-open. The TEDEE-PRO/GR smart lock is compatible with over 15 smart home systems (e.g. Apple HomeKit). To use these features, your TEDEE-PRO/GR device must be paired with the smart Tedee Bridge connected to the internet. When paired with the Tedee Keyboard, the lock can be opened with a PIN code.

Attention! To keep the existing cylinder and key, or to mount TEDEE-PRO/GR on a Nordic type lock, additional adapters are required (sold separately). The cylinder must have an emergency function.



Application:	opening and closing the lock
Compatible lock type:	 Dedicated cylinders of the Gerda SLR series, European cylinder with emergency function Adapter available : Nordic, American, European
Wireless:	Bluetooth, 2.4 GHz - BLE 5.0
Mobile phones support:	 The <u>Tedee</u> free application on Android The <u>Tedee</u> free application on iOS





Main features:	Remote control and management - Tedee application : - remote access, - Phone notification, - Activity log, - auto-open and close, - Setting scenarios by different events, - voice control • Bi-directional encrypted radio communication : TLS 1.3 • Secure virtual key - 256-bit data encryption • Remote opening of the door • lock button • Opening the door : manual, lock button, Tedee application • Jevels of access, password-protected • Compatibility with many smart home systems (e.g. Apple HomeKit, Google Assistant, Amazon Alexa, Homey, Fibaro, Grenton, eeDomus, Consolomio) • LED indication • Full compatibility with inward-opening doors • Compatibility with outward-opening doors : min. 30 mm (the distance between the cylinder axis and the door frame) • built-in battery • Low battery level alarm - Tedee application • Charging via USB cable with micro USB magnetic adapter • Battery charge indicator - Tedee application
Power supply:	Li-Poly battery 3000 mAh - Charging via micro USB port
Backup time:	6 10 months
Housing:	Aluminum
"Index of Protection":	IP20
Color:	Graphite + Black
Operation temp:	10 °C 40 °C
Permissible relative humidity:	max. 65 %
Weight:	0.196 kg
Dimensions:	• Ø 45 x 56 mm • 2 m - Length of the cable
Manufacturer / Brand:	GERDA / Tedee
Guarantee:	2 years

Mounting side view:







micro USB connector:





DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Micro USB magnetic adapter:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-05-09