

Code: DS-2CD2687G2T-LZS(2.8-12MM)(C)
IP VANDALPROOF CAMERA **DS-2CD2687G2T-LZS(2.8-12MM)(C)** ColorVu - 8.3 Mpx, 4K UHD
MOTOZOOM Hikvision

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

- 1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
- 2. Improper results of operation of the product or products related with it;
- 3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.





IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 8 MPx.

PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install.

Camera is according to IP67 Index of Protection norm.

Attention! The camera of the ColorVu series does not have a black and white mode. Thanks to fit the camera in a very sensitive sensor and the LED illuminator emitting visible light in white, the device allows to obtain a clear, colorful image in all lighting conditions.



Standard:	TCP/IP
Sensor:	1/1.8 " Progressive Scan CMOS
Matrix size:	8.3 Mpx
Resolution:	3840 x 2160 - 8.3 Mpx, 4K UHD , 3200 x 1800 - 5.8 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Lens:	2.8 12 mm Motozoom
View angle:	• 103 ° 40 ° (manufacturer data) • 96 40 ° (our tests result)
White light LED illuminator range:	60 m
Memory card slot:	Micro SD memory cards up to 512GB support (possible local recording)
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	1/1
Audio:	 External microphone input Audio output Bi-directional audio streaming support Noise suppression and echo cancellation Compliance with the AAC standard
Main stream frame rate:	25 fps @ 8.3 Mpx
Network interface:	10/100 Base-T (RJ-45)
WEB Server:	Built-in





Code: DS-2CD2687G2T-LZS(2.8-12MM)(C) IP VANDALPROOF CAMERA **DS-2CD2687G2T-LZS(2.8-12MM)(C)** ColorVu - 8.3 Mpx, 4K UHD MOTOZOOM Hikvision

Max. number of on-line users:	6
ONVIF:	✓
Main features:	The camera of the ColorVu series does not have a black and white mode Motozoom lens Possibility to turn off the LED illuminator WDR - 130 dB - Wide Dynamic Range 3D-DNR - Digital Noise Reduction ROI - improve the quality of selected parts of image Anti-Flicker - The technology eliminates the tiring eyes flickering image effect BLC - Back Light Compensation HLC - High Light Compensation (spot) NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its Possibility to change the resolution, quality and bit rate Horizontal mirror image Smart motion detection (with recognizing people and vehicles) Configurable Privacy Zones Sharpness - sharper image outlines video tampering Intelligent Image Analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <u>Hik-Connect</u> • iOS: Free application <u>Hik-Connect</u>
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply:	• PoE (802.3at), • 12 V DC / 1.2 A
Power consumption:	• ≤ 18 W @ PoE • ≤ 14.5 W @ 12 V DC
Housing:	Compact, Aluminum alloy
Color:	White
"Index of Protection":	IP67
Vandal-proof:	IK10
Operation temp:	-30 °C 60 °C
Weight:	1.46 kg
Dimensions:	298 x 98 x 96 mm



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-05-12 DS-2CD2687G2T-LZS(2.8-12MM)(C)



Code: DS-2CD2687G2T-LZS(2.8-12MM)(C)
IP VANDALPROOF CAMERA **DS-2CD2687G2T-LZS(2.8-12MM)(C)** ColorVu - 8.3 Mpx, 4K UHD
MOTOZOOM Hikvision

Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	311322055
Guarantee:	3 years



Side view:



Bottom view:






Code: DS-2CD2687G2T-LZS(2.8-12MM)(C)
IP VANDALPROOF CAMERA **DS-2CD2687G2T-LZS(2.8-12MM)(C)** ColorVu - 8.3 Mpx, 4K UHD
MOTOZOOM Hikvision



Memory card slot and "Reset" button:



Mounting side view:



Camera connectors:







Code: DS-2CD2687G2T-LZS(2.8-12MM)(C)
IP VANDALPROOF CAMERA **DS-2CD2687G2T-LZS(2.8-12MM)(C)** ColorVu - 8.3 Mpx, 4K UHD
MOTOZOOM Hikvision



Camera dimensions:







In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg