

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order.

If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
2. Improper results of operation of the product or products related with it;
3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The connector has been designed to ensure watertightness after crimping. During compression of the connector plastic bush is tightly pressed against the sheath of the cable (by putting on cone brass case - the compression ring). The plastic material is protected by patent Delrin of well known for quality of products DuPont company. It is UV-proof, and ensures stable physical parameters in very wide temperature range. The metal parts of the connector made of nickel-plated brass are corrosion-proof.

The connector is equipped with a plastic bush, which during compression of the connector is tightly pressed against the sheath of the cable (by putting on cone brass case - the compression ring). The dimensions are so matched that after compression connector is crimped on the cable sheath with a force so large that break the connector from the cable is impossible and so small that it does not damage the structure of the cable.

Quick and easy assembly, as well as stability of operation of the equipment are really worth the price.




Connector type:	"F" Plug
Attachment of connector elements:	Compression mounting
Application:	Coaxial cable
Frequency range:	0 GHz ... 3 GHz
VSWR:	< 1.1

Impedance:	75 Ω
Return loss:	30 dB
Wire mounting:	—
Cable diameter:	max. 6.8 mm
Shielding at 1GHz:	100 dB
Shield fastening:	Compression mounting
Plastic bush:	DuPont Delrin 527UV*
Material:	Brass (Nickel-plated)
Bush:	EPDM
Watertightness:	✓
Example of application:	Triset113
Main features:	<ul style="list-style-type: none"> • Wide frequency range • Watertightness of connector with cable connection • Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric • Very low loss in the whole operating band • Perfect matching to the transmission line within the whole operating band • Properly compressed connection is highly resistant to break • Many patent-pending solutions • To crimp use the crimping tool ZAC/PCT / ZAC/TR-255
Weight:	0.075 kg
Dimensions:	\varnothing 13 mm x 27 mm
Guarantee:	2 years

Preparation and termination of the cable (plug version with black plastic bush):



The TRISET-113 cable prepared for termination



Connector on the TRISET-113 cable, ready to compress



Connector crimped on the TRISSET-113 cable

Preparation and termination of the F/6.8-ZAC-PLAT connector on Triset-113 cable (plug version with black plastic bush):
:

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------